

# QUANTUM Q9000iP SERIES

## WEB BROWSER TELEPHONE ENTRY SYSTEM



Commercial application telephone entry system, programmable via Web Browser.

No "Monthly" fee on Web Browser Programming

No "Software Installation" necessary

Postal Lock Ready

Four way to program, via LAN, WAN, Direct Connect or System's Keypad.

Selectable port, no "Dedicated Static IP" needed.

Surface or Full-Flush Mount

FEATURES/MODEL	Q9000IP Surface Mount	Q9000IPFF Full-Flush Mount
Input Power	12Vac/12Vdc, 12Vac transformer included	12Vac/12Vdc, 12Vac transformer included
Current Consumption	1200mA	1200mA
Operating Temperature	0-140 °F	0-140 °F
Liquid Crystal Display	16 x 2, 9mm	16 x 2, 9mm
Backlit Keypad	Yes	Yes
Tenant Capacity	900	900
Access Code Capacity 4-8 Digit	900	900
Card/Keyfob Capacity	2000	2000
Number of Built-in Relay Form C Dry Contact	2	2
26-Bit Wiegand Input	Yes (1)	Yes (1)
Auto Unlock Schedule	10	10
Time Zone	10	10
Unlock Hold Using Card/Code	10 cards/10 codes	10 cards/10 codes
Holiday Time Zone	20	20
Temporary Card/Code up tp 10 Times Used	10 cards/10 codes	10 cards/10 codes
Programable Auxiliary Input	2	2
Door Sensor	2	2
Built-in Postal Lock Swich	Yes	Yes
Unlock Hold Timer	Yes	Yes
Event Recording/Report	1200 Buffer	1200 Buffer
Satellite Access Control Card Reader, Keypad, or Combo	Up to 8	Up to 8
Surface Mount Dimension (HxWxD)	13-9/16 " x 11-1/4 " x 3-3/4 "	
Full-Flush Dimension		Unit: 13-7/8" x 11-9/16" x 3-3/4" Trim Ring Inside: 13-3/4" x 12" x 3-11/16" Trim Ring Outside: 18" x 15-5/8"
Warranty	24 month	24 month

## ACCESSORIES

**QVPC** Analog color camera  
**USCR** 26-Bit Wiegand Satellite Card Reader  
**USKP** Satellite keypad  
**USKPR** Satellite Card Reader and Keypad Combination  
**UFOB** Quantum Keyfob  
**UCLAM** Quantum Clam Shell Card  
**UIISO** Quantum ISO Card  
**UCRM** 26-Bit Wiegand/RS-485 controller Module  
**UWCR** 26-Bit Wiegand Card Reader

[Pedestal Mounting Post, Adapter Plate and Mounting Ring](#)  
**UPM1S** Standard Single Arm (42"H, 5"x5" base)  
**UPM1L** Large Single Arm (47"H, 8"x8" base)  
**UPM6L** Large Single Arm (64"H, 8"x8" base)  
**UPM2** Double Vertical Arm (44"/84"H, 8"x8" base)  
**UPM5** Double Horizontal Arm (47"H, 8"x8" base)  
**UPM12E** 12" Expansion Arm use for all UPM  
**UPMDB64** Single Arm Direct Buriel (64"H)  
**UAP09** Adapter plate

[Miscellaneous Accessories](#)  
**USP1** AC and Telephone Surge Protector.  
**USP2L** Surge and Lighning Protection, *include Lightning on 24 months warranty*  
**UBAT1** 12VDC 4.5 Ahr backup battery.  
**UXIT** Multipurpose push button switch  
**IREXIT** Infrared exit switch  
**AHP5** Heater-pad