



- 600-2000 Tenants
- 2500-3500 cards and access codes
- Programming:
  - Local via Keypad or RS232
  - Remote via dial-up modem
- Programming and Data Management with AeGIS Management Software
- Event recording with 1200 events buffer.
- 2 x 16 Electronic Liquid Crystal Display (LCD)
- Two relays
- Non-Volatile Memory
- Auto Unlock Timer, Time Zones, and Holiday Time Zones
- Optional 26-Bit Wiegand Reader
- Indoor or outdoor, surface and full-flush mount
- Brushed Stainless Steel Face

*Warranty: 24 months*

### SPECIFICATIONS

**POWER INPUT:** 12VAC/40VA (supplied) or 12-VDC/40VA with battery backup charging circuit.

**CURRENT CONSUMPTION:** 700mA idle, 900mA operating.

**OPERATING ENVIRONMENT:** 32°F to 140°F. *Heater is required if the temperature is below 32°F.*

**NIGHT LIGHT:** Super Bright Light Emitting Diode (LED).

**COMMUNICATION:** 1200 Baud Modem, RS-485 and RS-232.

**CONSTRUCTION:** 16 Gauge Cold Rolled Steel back box with enamel finished and Brushed Stainless Steel Faceplate

**MOUNTING:** Surface and full-flush.

**DIMENSIONS:**

Surface 13-9/16"(H) x 11-1/4"(W) x 3-3/4"(D)

Full-flush 13-7/8" (H) x 11-9/16"(W) x 3-3/4" (D)

**MOUNTING RING FULL-FLUSH (FFM9 is included):**

Inside 13-3/4" (H) x 12" (W) x 3-11/16" (D)

Outside 18" (H) x 15-5/8" (W)

**SHIPPING WEIGHT:** 16 lb - 21 lb

*See quick guide or manual for further specifications*

### ORDERING PART

Surface Mount

**9600CR25P**

600 tenants 25000 cards/codes

**92KCR35P**

2000 tenants 3500 cards/codes

Full-flush Mount

**9600CR25FFP**

600 tenants 2500 cards and/or codes

**92KCR35FFP**

2000 tenants 3500 cards and/or codes

### ACCESSORIES

26-Bit Wiegand Proximity Readers and cards

**UWCR** Wiegand Proximity Reader.

**UIOS** credit card size (passive card)

**UCLAM** Clam Shell (passive card)

**UFOB** Key Fob (passive fob)

26-Bit Wiegand Radio Receiver and Transmitters

**AWRR** Radio Reader Receiver.

**AFOBT** Single Button Keyfob Transmitter.

**AFOBT2** Two Button Keyfob Transmitter.

**AHHT** Single Button Handheld Transmitter.

**AHHT2** Two Button Handheld Transmitter.

Satellite Systems

**USCR** RS-485 Satellite Card Reader

**USKP** RS-485 Satellite Keypad

**UCRM** 26 Bit Wiegand RS-485 Controller Module

Video Package

**UVPC** Color Camera Package.

**UVPB** Balun for twisted pair video transmission

Pedestal Mounting Post, Adapter Plate and Mounting Ring

**UPM1S** Standard Single Arm (42"H, 5"x5" base)

**UPM4S** Standard Single Arm (47"H, 5"x5" base)

**UPM1L** Large Single Arm (47"H, 8"x8" base)

**UPM6L** Large Single Arm (64"H, 8"x8" base)

**UPM8L** Large Single Arm (84"H, 8"x8" base)

**UPM2** Double Vertical Arm (44"/84"H, 8"x8" base)

**UPM5** Double Horizontal Arm (47"H, 8"x8" base)

**UPMDB64** Single Arm Direct Buriel (64"H)

**UPMDB72** Single Arm Direct Buriel (72"H)

**UAP09** Adapter Plate AeGIS 9000P Series

**UPM12E** 12" Expansion Arm use for all UPM

Miscellaneous Accessories

**FFM9** Full-flush mounting ring, *included w/ system*

**USP1** AC and Telephone Surge Protector.

**AHP5** Heater Pad with Thermostat.

**UBAT1** 12VDC 4.5 Ahr backup battery.

**AMDM** 56K Desktop/Laptop Modem

*Specifications subject to change without prior notice*